

JUL 2004

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number  
**WO 03/057938 A1**

(51) International Patent Classification<sup>7</sup>: C22C 49/00,  
B22F 7/06, C22C 47/06, E21B 10/56

(21) International Application Number: PCT/IB03/00030

(22) International Filing Date: 9 January 2003 (09.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02/0220 10 January 2002 (10.01.2002) ZA

(71) Applicant (for all designated States except US): **ELEMENT SIX (PTY) LTD** [ZA/ZA]; Debid Road, Nuffield, 1559 Springs (ZA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **TANK, Klaus** [ZA/ZA]; 9 Warbleton Avenue, Essexwold, 2007 Bedfordview (ZA).

(74) Agents: **KEMP, Mark et al.**; Spoor and Fisher, P.O. Box 41312, 2024 Craighall (ZA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MAKING A TOOL COMPONENT



(57) Abstract: In a method of producing a tool component a plurality of fibres is formed into a bundle. Each fibre has a core comprising a mass of ultra-hard abrasive particles or precursor to said ultra-hard abrasive particles and optionally a second phase, and a coating comprising a mixture of carbide particles and particulate binder metal. After extruding the bundle of fibres, the bundle is severed transverse to its length to produce a layer 24. The layer 24 is placed on a surface 26 of a substrate 28 and the layer 24 and substrate 28 are subjected to elevated temperature and pressure conditions at which the ultra-hard abrasive particles are crystallographically stable. The composition of the core and coating may be interchanged in the method.

WO 03/057938 A1